

Information

Traffic Shaping	
Shaping Throughput	1.2 Gbps
Concurrent Flow	260,000
New Connection Rate	11,000/s
Packets Per Second	260,000
Traffic Policies	1024
Traffic Shaping	
Acceleration Throughput	50 Mbps
Edge Cache Throughput	70 Mbps
Optimized Connections	9,000
Network Diagnostics	
APS Objects	250
SLA Objects	250
PDF Reports	60
Physical Characteristics	
Form Factor	1U rackmount
Dimensions (HxWxD)	438mm x 292mm x 44mm (17.52" x 11.68" x 1.76")
Power	150W Single PSU
Power Rating	TBD
Weight	6.3 kg

RAM	16 GB DDR4
Data Store/Cache Size	1TB SATA SSD 3D TLC
Environment	Continuous operation: 0 - 40°C (32 - 104°F), Humidity: 20 - 90% RH
Interface Capabilities	
Built in NICs	2 x 1G RJ45 bypass bridge pair, 2 x 1G SFP bridge pair
Additional NIC Slots	1 PCIe Gen3 x 8
Management Ports	RJ-45 serial console

Available NICs

Connector type LC

	EX-NIP-52123 <i>2-port 1 Gbps Multi-mode Short Range</i>	EX-NIP-52124 <i>2-port 1 Gbps Single-mode Long Range</i>
Connector type	LC	LC
Slot 1	Yes	Yes

Talk to an Exinda appliance expert today.

✉ sales@gfi.com 🌐 gfi.com/exinda