

Performance & Capacity

Feature	Specification
Number of users	10 - 20
Number of Devices	50 - 100
Concurrent Connections	3,000 - 4,000
Throughput Firewall	900 Mbps
Throughput UTM	460 Mbps
Supported Versions	v10 and later

System Specifications

Component	Specification
Processor	Intel(R) Atom(TM) x7211RE
Memory	8GB RAM
Storage	SSD 80GB
Security	TPM 2.0 onboard

Network Interfaces

Interface	Specification
LAN Ports	4 x 2.5GbE RJ45 ports

I/O Interfaces

Interface	Specification
USB	2 x USB 3.2, Type A; 1 x USB 3.2, Type C
Display Port	1 x DisplayPort
System Control	Power/Reset button
LED Indicators	LAN/MGMT/SYS/SSD/PWR

Physical Specifications

Feature	Specification
Dimensions	165 x 134.5 x 34 mm (6.5” x 5.3” x 1.3”)
Weight	0.715 kg (1.57 lb)
Design	Fanless desktop form factor

Power

Feature	Specification
Power Supply	36W 12V DC-in power adapter
Input	100-240V AC, 50-60 Hz

Environmental

Feature	Specification
Operating Temperature	0°C to 40°C (32°F to 104°F)
Storage Temperature	-20°C to 80°C (-4°F to 176°F)
Relative Humidity	10% to 90% non-condensing

Important Operational Information

Important Information	Specification
Auto Power-On	The appliance powers on immediately once the power cable is plugged in. No manual power button press is required.
DisplayPort Compatibility	Video output requires a direct DisplayPort to DisplayPort cable.
WARNING	The appliance will not boot if DisplayPort adapters (such as DisplayPort to HDMI) are connected.

Certifications

CE

FCC Class B

Package Contents

- NG120 Hardware Appliance.
- 36W 12V DC-in power adapter.
- Quick Start Guide.
- Ethernet Cable.

Copyright © 2025 GFI USA, LLC, All rights reserved.